IPC ASSOCIATION ELECTRONIC	© Copyright 2005.	Material Composition Declaration © Copyright 2005. IPC, Bannockburn, Illinois. All rights reservances international and Pan-American copyright conventions.		all rights reserved unontions.	der both	This document is a declaration of the substances within the manufacturer listed ite level parts, the declaration encompasses all lower level materials for which the ma					tem. Note:	if the item is an as r has engineering	sembly with lower responsibility.		
1752-21.1	IPC Web Site for Information on IPC-1752 Standard Form Typ http://www.ipc.org/IPC-175x Distribute				Declaration Class * Class 6 - RoHS Yes/No, Homogeneous Mater					ials and M	ials and Mfg Information				
Supplier	r Information														
Company name*			Company unique ID			τ	Unique ID Authority					Response Date*			
nsemi											2023-06-08				
Contact N	ame	Title - Contact			I	Phone - Contact*				Email - Contact*					
Product-l	Env-Stewards		Product Enviro Compliance				NA				Product-Env-Stewards@onsemi.com				
uthorize	d Representative*	Title - Representative			I	Phone - Representative*				Email - Representative*					
Product-Env-Stewards			Product Enviro Compliance				NA				Product-Env-Stewards@onsemi.com				
	Requester Item Number Mfr Iter		Number Mfr Item Name			Effective Dat	Date Version Manufacturing Site			Weight*	UOM	Unit Type			
		HCPL2631S 8PB 10M		8PB 10MB 2-CH S	PB 10MB 2-CH SMD		2023-06-08	023-06-08 THH		ГНН	542.964		mg	Each	
Manufa	cturing Process Informa	ation						•					·	·	
	Terminal Plating / Grid Array Material Terminal Base Alloy .			STD-020 MS	L Rating Peak Process Body Temperature Max Time at Peal					x Tempera	ture Num	ber of Reflow Cyc	eles		
Matte Tin (Sn) - annealed CU Alloy 1					225		C	30	seco	nds 3					
Comments	S														
vel 1 - m	aximum time at peak tempera	ture during sol	dering is 10-3	0 seconds											
or more	information regarding materia	l composition	please refer to	page 3											

RoHS Material Composition Declaration			Declaration Type *	Detail	led						
Directive 2015/863/EU amending RoHS Directive 2011/65/EU RoHS Definition: Quantity limit of 0.01% by mass (100 PPM) in homogeneous material for Cadmium and quantity limit of 0.1% by mass (1000 PPM) in homogeneous material for Lead (Pb), Mercury (Hg), Hexavalent Chromium (Cr6+), Polybrominated Biphenyls (PBB), Polybrominated Diphenyl Ethers (PBDE), and Bis(2-ethylhexyl) phthalate (DEHP), Benzyl-butyl phthalate (BBP), Dibutyl phthalate (DBP), Diisobutyl phthalate (DIBP).											
Please indicate whether any homogeneous material (as defined by the RoHS Directive, EU 2011/65/EU and implemented by the laws of the European Union member states) of the part identified on this form contains lead, mercury, cadmium, hexavalentchromium, polybrominated biphenyls and/or polybrominated diphenyl ethers (each a "RoHS restricted substance") in excess of the applicable quantity limit identified above. If a homogeneous material within the part contains a RoHS restricted substance inexcess of an applicable quantity limit, please indicate below which, if any, RoHS exemption you believe may apply. If the part is an assembly with lower level components, the declaration shall encompass all such components. Supplier certifies that it gathered the information it provides in this form using appropriate methods to ensure its accuracy and that such information is true and correct to the best of its knowledge and belief, as of the date that Supplier completes this form. Supplier acknowledges that Company will rely on this certification in determining the compliance of its products with European Union member state laws that implement the RoHS Directive. Company acknowledges that Supplier may have relied on information provided by others in completing this form, and that Supplier may not have independently verified such information. However, in situations where Supplier has not independently verified information provided by others, Supplier agrees that, at a minimum, its provided certifications regarding their contributions to the part, and those certifications are at least as comprehensive as the certification in this paragraph. If the Company and the Supplier enter into a written agreement with respect to the identified part, the terms and conditions of that agreement, including any warranty rights and/or remedies provided as part of that agreement, will be the sole and exclusivesource of the Supplier's Standard Terms and Conditions of Sale applicable to such part shall apply.											
RoHS Declaration * 1 - Item	(s) does not contain RoHS restricted substa	ances per the definition above	Supplier Ac	cceptance *	Accepted						
Exemption: If the declared item does not contain RoHS restricted substances per the definition above except for defined RoHS exemptions, then select the corresponding response in the RoHS Declaration above and choose all applicable exemptions.											
Exemption List Version	EL-2011/534/EU										
Declaration Signature											
Instructional Complete all of the required	fields on all neggs of this form. Calcut th		a duan dawn. This will display the signature on	a Digitally sign	the declaration (if recurined by the						
Instructions: Complete all of the required Requester) and click on Submit Form to			e drop-down. This will display the signature ar	ea. Digitally sign	the declaration (if required by the						

Homogeneous Material Composition Declaration for Electronic Products

SubItem Instructions: The presence of any JIG Level A or B substances must be declared. [1] indicate the subpart in which the substance is located, [2] provide a description of the homogeneous material [3], enter the weight of the homogeneous material.

Substance Instructions: [A] select the Level (JIG A, JIG B, Requester or Supplier) [B] select the substance category (JIG or Requester) or enter a value (Supplier). [C] select the substance (JIG) or enter the substance and CAS (Other). [D] select a RoHS exemption, if applicable [E] enter the weight of the substance or the PPM concentration [F] Optionally enter the positive (+) and negative (-) tolerance in percent (Note: percent tolerance values are expected to cover a 3 sigma range of distribution unless otherwise noted).

Homogeneous Material	Weight	Unit of Measure	Level	Substance	CAS	Exempt	Weight	Unit of Measure
Coupling Gel	64.0	mg	Supplier	3-Methacryloxypropyltrimethoxysilane (C10H20O5Si)	2530-85-0		64	mg
Die	0.099	mg	В	Gallium Arsenide (AsGa)	1303-00-0		0.033	mg
			Supplier	Silicon (Si)	7440-21-3		0.066	mg
Die Attach	0.25	mg	Supplier	Silver (Ag)	7440-22-4		0.2075	mg
			Supplier	Ortho Cresol Novolac Resin	29690-82-2		0.0425	mg
Lead Frame	115.0	mg	Supplier	Zinc (Zn)	7440-66-6		0.138	mg
			Supplier	Iron (Fe)	7439-89-6		2.7125	mg
			Supplier	Copper (Cu)	7440-50-8		112.125	mg
			Supplier	Phosphorus (P)	7723-14-0		0.0245	mg
Mold Compound-Black	93.303	mg	Supplier	Brominated Epoxy Resin-2	68541-56-0		2.3325	mg
			Supplier	Ortho Cresol Novolac Resin	29690-82-2		13.995	mg
			В	Antimony Trioxide (Sb2O3)	1309-64-4		1.866	mg
			Supplier	Carbon Black (C)	1333-86-4		0.4695	mg
			Supplier	Fused Silica (SiO2)	60676-86-0		65.31	mg
			Supplier	Phenolic Resin (Novolac)	9003-35-4		9.33	mg
Mold Compound-White	258.662	mg	Supplier	Titanium Dioxide (TiO2)	13463-67-7		52.4	mg
			Supplier	Zirconium Dioxide (ZrO2)	1314-23-4		1.3	mg
			Supplier	Ortho Cresol Novolac Resin	29690-82-2		196.662	mg
			Supplier	Silica Amorphous (SiO2)	7631-86-9		5.6	mg
			Supplier	Aluminum Trioxide (Al2O3)	1344-28-1		2.7	mg
Plating	11.6	mg	Supplier	Tin (Sn)	7440-31-5		11.6	mg
Wire Bond - Au	0.05	mg	Supplier	Gold (Au)	7440-57-5		0.05	mg